



\* TO MATCH 24" CURB & GUTTER, SLOPE = 1" : 32"  
 TO MATCH 30" CURB & GUTTER, SLOPE = 1" : 24"

NOTES:

1. FOR USE ON STREETS HAVING A 45 MPH OR GREATER SPEED LIMIT.
2. CRACK CONTROL JOINTS TO BE PROVIDED AT ENTRANCE MIDDLE AND AT ENTRANCE DIAGONALS BY SAWING, SCORING, "LEAVE-IN" INSERTS, OR CUTTER PLATES TO 1-1/2 INCH DEPTH.
3. STREET APPROACH TO BE POURED MONOLITHICALLY WITH RADIAL CURB.
4. FOR CURBED STREETS WITHOUT SIDEWALKS OR FOR USE WITH A HIGH VOLUME ENTRANCE WITH OPTIONAL HANDICAP RAMP WHEN DIRECTED BY LOCALITY.
5. WATER METERS AND SEWER CLEANOUTS SHALL NOT BE LOCATED IN DRIVEWAY (ENTRANCE) OR APRON UNLESS AUTHORIZED BY OWNER.
6. CONCRETE REINFORCEMENT METHOD PER CONTRACT DOCUMENTS.

## HIGH TRAFFIC SPEED COMMERCIAL ENTRANCE

NOT TO SCALE

REFERENCE	CATEGORY	DATE	SHEET No.	DETAIL No.
200,502	CONCRETE ITEMS	6/16	1 OF 1	CI_06